

SLIMLINE LITE II™ 17.0 SMART CARD READER

Rack Drawer Flip-up LCD Monitor/Keyboard/Trackball with Built-in Common Access Card Reader



In addition to its standard flip-up display with integral keyboard and trackball, this rugged SlimLine Lite II features a built-in, USB-powered Smart Card (CAC) reader for areas where secure access is essential.

The compact enclosure can be configured as a “laptop,” or equipped with solid-bearing locking slides for rack mounting.

At only 2U (3.50”) high, the low profile design and industrial durability combine with General Digital’s legendary configuration control to create a product with a long life cycle.

The SlimLine Lite II Series is used in many industrial and military environments alike.

The Smart Card reader is placed for easy access by authorized personnel



FEATURES

- » 17.0” LCD, 1280 x 1024 resolution
- » Built-in, front-mounted Common Access Card (Smart Card) reader
- » VGA, DVI-D, Composite video inputs
- » Low profile 2U (3.50”) and 20” rack depth
- » Rugged aluminum construction with durable finish is designed to be in compliance with MIL-DTL-901E, MIL-STD-810, MIL-STD-167 and more
- » Designed, manufactured and serviced in the USA

OPTIONS

- » Additional display sizes: 15.0”, 17.3”, 19.0”, 20.1”
- » Compliance with radiated and conducted EMI requirements (e.g., MIL-STD-461, TEMPEST)
- » Sunlight readable and MIL-STD-3009 NVIS-compatible display backlights
- » Keyboard/trackball options: environmental sealing, colored keycaps and backlights, custom firmware
- » Solid-bearing, locking slides for mounting directly to EIA-310 RETMA 19” racks
- » Power supplies, DC-DC converters
- » Extended warranties

SLIMLINE LITE II™ 17.0 SMART CARD READER

SPECIFICATIONS

| | |
|-------------------------------------|---------------------------------------|
| Display Size | 17.0" |
| Resolution | 1280 x 1024 |
| Number of Colors | 16.7 Million |
| Luminance | 350 nits |
| Contrast | 1000:1 |
| Viewing Angle (Horizontal/Vertical) | ±85/±85° |
| Operating Temperature | -30° to 85°C |
| Video Input | VGA, DVI-D, Composite |
| Other | Front-mounted Smart Card (CAC) reader |



*Information Systems Technician
3rd Class Ashley Adams operating a
SlimLine Lite II aboard the USS America.
Photo by Mass Comm. Specialist 3rd Class Vance Hand*

999-0902-011r1



An SBA Small Business Concern

60 Prestige Park Road

East Hartford, Connecticut 06108

Phone 860.282.2900 | Toll-Free 800.952.2535

E-mail gdc_info@generaldigital.com



DISCLAIMER

Information contained in this document is proprietary to General Digital Corporation and is current as of publication date. This document may not be modified in any way without the express written consent of General Digital. Product processing does not necessarily include testing of all parameters. General Digital reserves the right to change the configuration and performance of the product and to discontinue product at any time. **The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.**

© 2020 General Digital Corporation. All rights reserved.

All product names are trademarks of their respective companies.