

# TITAN™ STANDALONE 64.5

Industrial-/Military-grade Large Format 65" LCD Monitor



**Titan Series** monitors satisfy the increased demands for information density.

The rugged aluminum standalone/mountable enclosure provides superior protection to the monitor's sensitive display and electronics, and facilitates simple mounting in your panel or kiosk. Titan is designed to be in compliance with numerous military standards.

The standard issue Titan Standalone 64.5 operates from a single +24V regulated source. Multiple power supply configurations are offered; or the customer can provide their own power source.

## FEATURES

- » 64.5" high resolution display with 4000:1 CR
- » ARGB, DVI, HDMI, DP, S-Video, Composite, Component
- » Rugged and shielded to be in compliance with many military standards, including 901E, 810G, 461F, 167B
- » Polycarbonate EMI-shielded display overlay for low electromagnetic emissions and susceptibility
- » Integrated 15 W stereo speakers and IR remote control
- » Front-accessible USB port
- » Rear and side VESA mounting facilitates customer integration

## OPTIONS

- » Multiple other video inputs
- » Fiber optic video
- » Capacitive, resistive, multitouch and other touch screen technologies
- » Integrated cable TV tuner
- » Remote control over IP
- » Much more

# TITAN™ STANDALONE 64.5

## BASE UNIT SPECIFICATIONS (STANDARD CONFIGURATION)

Display Size	64.5"
Resolution	1920 x 1080
Number of Colors	1.07 Billion
Luminance	360 nits
Contrast (maximum)	4000:1
Viewing Angle (Horizontal/Vertical)	±89°/±89°
Operating Temperature	0° to 50°C
Video Input	DVI-D (x2), HDMI, DisplayPort, ARGB, Component, Composite, S-Video (x2)
Power Input	+24 Vdc
Shock	50 G, 11 ms ½ Sine Wave
Vibration	1.0 G (10–200 Hz)
Special Features	Dual Front-mounted 15 W Speakers, 3.5mm Audio Jack, Front-mounted USB Port



60 Prestige Park Road

East Hartford, Connecticut 06108

Phone 860.282.2900 | Toll-Free 800.952.2535

E-mail [gdc\\_info@generaldigital.com](mailto:gdc_info@generaldigital.com)



999-0902-017r1

### DISCLAIMER

Information contained in this document is proprietary to General Digital Corporation and is current as of publication date. This document may not be modified in any way without the express written consent of General Digital. Product processing does not necessarily include testing of all parameters. General Digital reserves the right to change the configuration and performance of the product and to discontinue product at any time. **The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.**

© 2021 General Digital Corporation

All product names are trademarks of their respective companies.