



3mm GLASS
ANTI-GLARE ETCH

OSD KEYPAD/BRIGHTNESS
CONTROL

MOUNTING HOLES:
Ø0.218 THRU,
COUNTERSINK
Ø0.397 x 100° (X30)

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL DIGITAL AND IS NOT TO BE DISCLOSED, REPRODUCED OR PUBLISHED WITHOUT WRITTEN CONSENT FROM GENERAL DIGITAL. THIS DOCUMENT MUST BE RENDERED ILLEGIBLE WHEN BEING DISCARDED. © COPYRIGHT 2015. ALL RIGHTS RESERVED.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
FRACTIONS DECIMALS ANGLES
±1/32 .X ±.050 ±0° 30'
.XX ±.031
.XXX±.020

CONNECTOR CHART

DESIGNATION	FUNCTION	TYPE
CN1	AC INPUT	IEC-320
CN2	SERIAL INPUT	DE-9-S
CN3	ANALOG VIDEO INPUT	DE-15-S
CN4	DVI-D INPUT	DVI-I

MECHANICAL OUTLINE ONLY.
SPECIFICATIONS SUBJECT TO
CHANGE WITHOUT NOTICE. U.O.S.
ALL DIMENSIONS ARE IN INCHES.

APPROVALS	DATE
DRAWN G.L.	02-Aug-17
CHECKED T.R.	
APPROVED J.H.	

DO NOT SCALE DRAWING



60 Prestige Park Road, East Hartford, CT 06108
860.282.2900 www.GeneralDigital.com

SABER PANELMOUNT 20.1" UXGA MONITOR

B	CAGE CODE	DWG. NO.	REV
	1JA77	950-008-97	-