



OVERLAY: 3.4mm LAMINATED EMI FILTER/HEATER ANTI-REFLECTIVE FRONT SURFACE

7-BUTTON BACKLIT OSD KEYPAD

WORKSTATION POWER SWITCH W/ FINGER GUARD & SEALING BOOT

LED STATUS INDICATORS

BALL DETENT FOR GRIMES LIGHT MOUNTING

PROGRAMMING PORT W/ EMI COVER

PRESSURE RELIEF VALVE

PROVISIONAL HEAT SINK, DEPENDENT ON INTERNAL TESTING. HEAT SINK HEIGHT NOT TO EXCEED 0.500" FROM REAR COVER.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL DIGITAL AND IS NOT TO BE DISCLOSED, REPRODUCED OR PUBLISHED WITHOUT WRITTEN CONSENT FROM GENERAL DIGITAL. THIS DOCUMENT MUST BE RENDERED ILLEGIBLE WHEN BEING DISCARDED. © COPYRIGHT 2019. ALL RIGHTS RESERVED.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES  
 TOLERANCES ARE:  
 FRACTIONS DECIMALS ANGLES  
 ±1/32 .X ±.050 ±0° 30'  
 .XX ±.031  
 .XXX±.020

CONNECTOR CHART		
DESIGNATION	FUNCTION	TYPE
J1	DIGITAL I/O PORT	D38999/24WC35BN
J2	3-PHASE POWER INPUT	D38999/24WB98PN
J3	VIDEO I/O PORT	TV07RGW21-11PLC
J5	BULLNOSE POWER OUTPUT	D38999//24WA35BN
J6	PROGRAMMING PORT	DE-9-P
GND	GROUND STUD (1/2" LONG)	#10-32 UNF-2A

MECHANICAL OUTLINE ONLY. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. U.O.S. ALL DIMENSIONS ARE IN INCHES.	
APPROVALS	DATE
DRAWN G.L.	29-Aug-19
CHECKED J.H.	
APPROVED S.B.	
<b>DO NOT SCALE DRAWING</b>	



60 Prestige Park Road, East Hartford, CT 06108  
 860.282.2900 www.GeneralDigital.com

**SABER STANDALONE  
 21.3" QSXGA MONITOR**

<b>B</b>	CAGE CODE	DWG. NO.	REV
	1JA77	3213-005-97	-