# SLIMLINE 1U<sup>™</sup> 17.3 BRD-KVM-USB-PS

Rack Drawer Flip-up LCD Monitor/Keyboard/Trackball with Blu-ray® Drive & KVM Switch

In addition to its standard flip-up display with integral keyboard and trackball, this rugged SlimLine 1U features a wide-screen 17.3" display, built-in Blu-ray® drive and 2-port KVM switch for your multimedia needs.

At only 1.75" high, the ultra-compact design and industrial durability combine with General Digital's legendary configuration control to create a product with a long life cycle.

> The SlimLine 1U Series is well suited to industrial and military environments alike.

The compact SlimLine 1U is equipped with a power supply and 2-port KVM switch on the back and a Blu-ray® drive on the front





### **FEATURES**

- » 17.3" LCD, 1920 x 1080 resolution
- » Integrated Blu-ray<sup>®</sup> drive also plays CDs and DVDs
- » VGA, DVI-D video inputs
- » Low profile 1U (1.75") and 28" rack depth
- » Integrated 2-port KVM switch and power supply
- » Integrated 4-port USB hub enables use of only one interface cable to connect to host computer
- » Mounts directly to EIA-310 RETMA 19" racks via solidbearing, locking slides
- » Rugged aluminum construction with durable finish is designed to be in compliance with MIL-DTL-901E, MIL-STD-810, MIL-STD-167 and more
- » Designed, manufactured and serviced in the USA

### **OPTIONS**

- » Additional display sizes include 15.0", 17.0" and 19.0"
- » Compliance with radiated and conducted EMI requirements (e.g., MIL-STD-461, TEMPEST)
- » Sunlight readable and MIL-STD-3009 NVIS-compatible display backlights
- » Keyboard/trackball options: environmental sealing, colored keycaps and backlights, custom firmware
- » Smart Card (CAC) readers
- » Speakers, headphone jacks
- » Power supplies, DC-DC converters
- » Extended warranties



# SLIMLINE 1U<sup>™</sup> 17.3 BRD-KVM-USB-PS

#### **SPECIFICATIONS**

Display Size	17.3″
Resolution	1920 × 1080
Number of Colors	16.7 Million
Luminance	400 nits
Contrast	600:1
Viewing Angle (Horizontal/Vertical)	±80/+60°, -80°
Operating Temperature	0° to 70°C
Video Input	VGA, DVI-D
Other	Blu-ray <sup>®</sup> drive, 2-port KVM switch, 4-port USB Hub



1:2015

QUALITY

MANAGEMENT

SYSTEM

CERTIFIED

## GENERAL DIGITAL

60 Prestige Park Road

East Hartford, Connecticut 06108

Phone 860.282.2900 | Toll-Free 800.952.2535

E-mail gdc\_info@generaldigital.com

#### DISCLAIMER

999-0902-016r1

Information contained in this document is proprietary to General Digital Corporation and is current as of publication date. This document may not be modified in any way without the express written consent of General Digital. Product processing does not necessarily include testing of all parameters. General Digital reserves the right to change the configuration and performance of the product and to discontinue product at any time. **The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.** 

© 2020 General Digital Corporation. All rights reserved. All product names are trademarks of their respective companies.