TwoView 2 Vertical[®] Series

Rack Drawer Dual Vertical Flip-up LCD Monitors with Keyboard and Trackball



The **TwoView 2 Vertical** is designed to provide its operator the maximum amount of visual information with the smallest horizontal footprint.

The vibrant, high performance displays can be positioned at a variety of angles to minimize operator strain.

The 2U high all-metal enclosure is designed and built to provide years of reliable service.

FEATURES

- » Two high resolution LCDs (17.3" or 19.0") provide twice the data content as a standard single rack mount display device
- » Many commercial-grade keyboards with pointing device available
- » Low profile 2U (3.50") rack height when stowed
- » VGA, DVI-D, HDMI, DisplayPort video inputs
- » Locking HDMI connectors
- » 80-264 Vac input power supply
- » Easy access dual OSD keypads on keyboard tray
- » Solid-bearing locking slides for direct mount to EIA-310 RETMA 19" racks
- » Rugged construction with durable finish designed to be industrial compliant
- » Designed, manufactured and serviced in the USA

The rear connector panel on the TwoView 2 Vertical includes separate video inputs for each display.

OPTIONS

- » Keyboard/trackball options: environmental sealing, colored keycaps and backlights, custom firmware
- » Compliance with radiated and conducted EMI requirements (e.g., MIL-STD-461, TEMPEST)
- » Sunlight readable and MIL-STD-3009 NVIS-compatible display backlights
- » Power supplies, DC-DC converters
- » Additional display sizes available
- » Extended warranties





TwoView 2 Vertical[™] Series

SPECIFICATIONS (STANDARD CONFIGURATION)

| Display Size | 17.3″ | 19.0″ |
|-------------------------------------|-------------------------------|-------------------------------|
| Resolution | 1920 × 1080 | 1280 × 1024 |
| Number of Colors | 16.7 Million | 16.7 Million |
| Luminance | 400 | 450 nits |
| Contrast | 600:1 | 1000:1 |
| Viewing Angle (Horizontal/Vertical) | ±80°/+60°, -80° | ±85°/±80° |
| Operating Temperature | 0° to 70°C | -30° to 85°C |
| Video Input | VGA, DVI-D, HDMI, DisplayPort | VGA, DVI-D, HDMI, DisplayPort |
| | | |



1:201

QUALITY

MANAGEMENT

SYSTEM

CERTIFIED

GENERAL DIGITAL

60 Prestige Park Road

East Hartford, Connecticut 06108

Phone 860.282.2900 | Toll-Free 800.952.2535

E-mail gdc_info@generaldigital.com

DISCLAIMER

999-0902-020r5

Information contained in this document is proprietary to General Digital Corporation and is current as of publication date. This document may not be modified in any way without the express written consent of General Digital. Product processing does not necessarily include testing of all parameters. General Digital reserves the right to change the configuration and performance of the product and to discontinue product at any time. **The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.**

© 2020 General Digital Corporation All product names are trademarks of their respective companies.