

Ø0.157 THRU, COUNTERSINK Ø0.315 x 90° (X16)

OVERLAY: RESISTIVE TOUCH SENSOR W/ LAMINATED EMI SHIELD


8-BUTTON KEYPAD

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF GENERAL DIGITAL AND IS NOT TO BE DISCLOSED, REPRODUCED OR PUBLISHED WITHOUT WRITTEN CONSENT FROM GENERAL DIGITAL. THIS DOCUMENT MUST BE RENDERED ILLEGIBLE WHEN BEING DISCARDED. © COPYRIGHT 2015. ALL RIGHTS RESERVED.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
 TOLERANCES ARE:
 FRACTIONS DECIMALS ANGLES
 ±1/32 .X ±.050 ±0° 30'
 .XX ±.031
 .XXX±.020

CONNECTOR CHART		
DESIGNATION	FUNCTION	TYPE
CN1	ANALOG VIDEO INPUT	D38999/24WB35SN
CN2	DVI INPUT	805-024-07ZW12-265A-518
CN3	TOUCH (USB) OUTPUT	D38999/24WA35SN
CN4	+9 - +36 VDC INPUT	D38999/24WA98SN
GND	GROUND STUD (1/2" LONG)	10-32 UNF-2A

MECHANICAL OUTLINE ONLY. SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. U.O.S. ALL DIMENSIONS ARE IN INCHES.	
APPROVALS	DATE
DRAWN G.L.	03-Nov-17
CHECKED -	-
APPROVED -	-
DO NOT SCALE DRAWING	



GENERAL DIGITAL
The Innovators of Flat Panel Technology
 8 Nutmeg Road South, South Windsor, CT 06074
 (860) 282-2900 www.GeneralDigital.com

BARRACUDA PANELMOUNT
21.5" WUXGA MONITOR

B	CAGE CODE 1JA77	DWG. NO. 3215-021-97	REV A1
----------	--------------------	-------------------------	-----------