

SABER PANELMOUNT™ 24.0 FO-DVI

Military-grade LCD Monitor with Integrated Fiber Optic to DVI Video Receiver

The military-spec Saber PanelMount 24.0 features the largest LCD (24.0") available in our Saber lineup. This unit comes equipped with an optically-bonded vandal shield for shock resistance and an EMI overlay for suppression of electrical interference. The purpose-built and cost-effective rugged enclosure is ready for duty.



Mil-spec Saber PanelMount 24.0 includes a ½" thick front bezel, mil-grade connectors, and rear louvers to protect fans



FEATURES

- » High resolution (1920 x 1080) 24.0" LCD
- » Micromesh EMI shield to minimize electrical interference
- » Front surface is chemically strengthened to produce an effective shock-resistant vandal shield
- » Optically-bonded and antireflective overlay
- » Integrated fiber optic-to-DVI video receiver
- » Military D38999 connectors for fiber optic video/power
- » Designed to be in compliance with MIL-STD-901D, MIL-STD-810F, MIL-STD-461E/F, MIL-STD-167B, more
- » Ruggedized aluminum panel mount enclosure
- » Rear louvers for drip protection of cooling vents and fans
- » Sealed for 100% non-condensing humidity
- » Federal Standard gray finish

OPTIONS

- » Optional stainless steel bezel/enclosure and choice of powder coat paint, including Federal Standard and custom colors
- » Multitouch touch screen technologies
- » Wide variety of video inputs, including VGA, DVI, HDMI, SD-SDI, HD-SDI, DisplayPort, more
- » NVIS filters, circular polarizers, ¼-wave retarders, AC and DC custom power supplies, media players, speakers, more

SABER PANELMOUNT™ 24.0 FO-DVI

SPECIFICATIONS

Display Size	24.0"
Viewing Area (W x H)	518.4 x 324.0 mm
Resolution	1920 x 1200
Number of Colors	16.7 million (6-bit + Hi-FRC)
Luminance	220 nits
Contrast	1000:1
Response Time	2 ms
Viewing Angle (Horizontal/Vertical)	±85°/±80°
Operating Temperature	0° to 60°C
Glass	Optically-bonded Vandal Shield, Antireflective, Micromesh 2 EMI Shielded
Video Input	Standard: VGA–WUXGA Alternate: Internal Fiber Optic to DVI Receiver
Other	Enclosure IP65 Sealed, Cooling Fans Environmentally Sealed with Louvers for Extra Protection, Federal Standard Gray Paint 26307

David Mark/Pixabay



999-0902-009r1

 **GENERAL
DIGITAL**
An SBA Small Business Concern

60 Prestige Park Road

East Hartford, Connecticut 06108

Phone 860.282.2900 | Toll-Free 800.952.2535

E-mail gdc_info@generaldigital.com



DISCLAIMER

Information contained in this document is proprietary to General Digital Corporation and is current as of publication date. This document may not be modified in any way without the express written consent of General Digital. Product processing does not necessarily include testing of all parameters. General Digital reserves the right to change the configuration and performance of the product and to discontinue product at any time. **The appearance of U.S. Department of Defense (DoD) visual information does not imply or constitute DoD endorsement.**

© 2020 General Digital Corporation. All rights reserved.

All product names are trademarks of their respective companies.