

TABLE I - WIRE CONNECTIONS							
P1	P2	Signal	Color				
P1-A1	P2-A1	+12 VDC	Red				
P1-A2	P2-A2	GND	Black				
Shell	Shell	Shield	Shield				



HIS DOCUMENT CONTAINS PROPHIETARY INFORMATION OF GENERAL DIGITAL AND IS NOT TO BE DISCLOSED, REPRODUCED OR PUBLISHED WITHOUT WRITTEN CONSENT FROM GENERAL DIGITAL. THIS DOCUMENT MUST BE RENDERED ILLEGIBLE WHEN BEING DISCARDED.					STANDED CABLE DRAWING			
CABLE LENGTH	TOLERANCE	В	APPROVAL	DATE 12/09/20	DC EXT Cable, 2W2 Plug to 2W2 Plug, Braid Shield, 50.0"			
<1"	± 1⁄16"		MK		FILE	DWG. NO.		REV
1"-2"	± 1/8 "		DRAWN	DATE 12/07/20	200-003-066	200-003-066		-
2"-18"	± 1⁄4 "		MM		200 000 000			
18"-72"	±½"		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS NOTED IN CHART		DO NOT SCALE DRAWING	CAGE CODE	SHEET	2
>72"	± 2%					1JA77	(OF <u></u>